

EK CAM CHAIN LIST

Part No.	Pitch (mm)	Bush/Roller Outer Diameter (mm)	Inner Link inner width(mm)	Pin Outer Diameter (mm)	Pin Length (mm)	Plate Thickness (mm)	Plate Height (mm)	tension strength kN	Weight (1m) (Kg)	Features
25	6.350	3.300	3.10	2.30	7.60	0.75	6.00	4.40	0.13	
25H	6.350	3.300	3.10	2.30	8.60	1.00	6.00	5.50	0.16	
29H	7.774	4.585	4.60	3.16	11.90	1.40	7.50	9.80	0.32	
06B	9.525	6.350	5.72	3.25	12.30	1.30	8.10	10.30	0.39	
06B-2	9.525	6.350	5.72	3.25	23.00	1.30	8.10	21.10	0.77	
06BE	9.525	6.350	5.72	3.25	13.60	1.35	8.30	12.40	0.45	Solid Bush、Chromizing Pin
05E	8.000	6.650	4.60	3.16	11.70	1.30	7.80	10.30	0.36	
05T-D	8.000	4.700	4.60	3.16	11.50	1.30	7.80	8.50	0.42	Solid Bush
05T-M	8.000	4.700	4.60	3.16	11.50	1.30	7.80	8.20	0.42	

Bush Chain =Bush Outer Diameter